XLIFT XLF-500

Front Load

Built for Heavy-Duty Performance

Designed for demanding professional applications, the XLIFT 500 combines strength, stability and ease of handling in a robust lifting solution.

Its five-section aluminium mast is equipped with the Safety Stop system on every section, ensuring maximum operator safety throughout every lifting operation. Integrated eyebolts on each mast section allow the lifter to be securely fixed at any working height. The heavy-duty steel base, fitted with four swivel castors, provides smooth positioning and effortless manoeuvrability.

As standard, the XLIFT 500 also includes two rear transport wheels and a central wheel, allowing quick and convenient horizontal transportation between working locations.



Maximum Load (WLL)	→	500 kg - Structural mode: 1200 kg
Minimum Load	→	25 kg
Maximum Height	→	7 m
Folded Height	→	1.90 m
Unit Weight	→	223 kg
Winch	→	1200 kg
Adaptor	→	Ø50 mm
Security	→	Exclusive Lock System

The values and configurations shown are indicative only and may vary depending on the installation conditions.
Every installation must be designed, ballasted and verified in accordance with the applicable regulations.

Accessories



LIXPS-1TR

U Piece for longitudinal load



LIXPS-2TR

U Piece for transverse load



LIXFAS-01

Special support to lift PA systems with forks