XLIFT XLT-150

Top Load

Compact Footprint. Professional Performance.

Offering greater lifting height while maintaining a compact design, the XLIFT 150 is the ideal solution for a wide range of professional applications.

With a maximum lifting capacity of 150 kg and a lifting height of up to 5.35 m, it delivers outstanding performance in a compact package. When folded, it measures just 1.70 m in height, making transport and storage quick and convenient.

Its square steel base, fitted with four swivel castors, ensures excellent stability together with precise positioning and smooth manoeuvrability during setup operations.



Maximum Load (WLL)	→	150 kg
Minimum Load	→	25 kg
Maximum Height	→	5.35 m
Folded Height	→	1.7 m
Unit Weight	→	41 kg
Winch	→	450 kg
Adaptor	→	Ø35 mm
Security	→	Exclusive Lock System

The values and configurations shown are indicative only and may vary depending on the installation conditions.
Every installation must be designed, ballasted and verified in accordance with the applicable regulations.

Accessories



LIXPSU-06B

TRUSS BRACKET
Black truss support, with U-piece and pin.
Insertion of Ø35 mm



LIXBT-06B

LIGHTING BAR
Support bar with lenght of 1.89 m.
Suitable for all towerlifts with insertion of Ø35 mm

