XLIFT
XLT-125

Top Load

Compact, Lightweight and Ready to Lift

The most cost-effective model in the XLIFT range, the XLIFT 125 delivers reliable lifting performance in an exceptionally compact and lightweight design.

With a lifting capacity of up to 125 kg and a weight of just 21 kg, it is easy to transport and handle. When folded, it measures only 1.26 m in length, making it ideal for applications where space and portability are essential. Equipped with the Lock System anti-fall device, the XLIFT 125 provides the same high level of safety found across the entire XLIFT range.



Maximum Load (WLL)	→	125 kg
Minimum Load	→	25 kg
Maximum Height	→	3.8 m
Folded Height	→	1.26 m
Unit Weight	→	21 kg
Winch	→	450 kg
Adaptor	→	Ø35 mm
Security	→	Exclusive Lock System

The values and configurations shown are indicative only and may vary depending on the installation conditions.
Every installation must be designed, ballasted and verified in accordance with the applicable regulations.

Accessories



LIXPSU-06B

TRUSS BRACKET
Black truss support, with U-piece and pin.
Insertion of Ø35 mm



LIXBT-06B

LIGHTING BAR
Support bar with lenght of 1.89 m.
Suitable for all towerlifts with insertion of Ø35 mm

